



HiFiBerry Digi+ transformer version

The HiFiBerry Digi+ transformer version is a high-quality S/PDIF output board for the Raspberry Pi (newer models with 40 pin GPIO connector). Additionally to the standard version, it features a fully galvanic isolation of the electrical output.


Facts

- Dedicated S/PDIF interface chip supports up to 192kHz/24bit resolution
- Optical (Toslink) and electrical outputs
- Full galvanic isolation between the Raspberry Pi and your DAC on the electrical output
- Bit-perfect output, audio data stream will not be modified in any way
- Connects directly to the Raspberry Pi, no additional cables needed
- No soldering, comes as a pre-fabricated kit. You just plug it onto the Raspberry Pi, it is conform to the Raspberry Pi hardware-attached-on-top (HAT) specification.
- Compatible with Raspberry Pi models A+,B+, 2B and 3B
- Directly powered from the Raspberry Pi, no additional power supply
- Comes with all components required to mount it. We include 4 M2.5x12mm spacers to fix the board onto the Raspberry Pi.

Dimensions without package	5.5 x 6.5 x 2 cm
Dimensions including package	9.5 x 7.5 x 2.5 cm
Weight	0.02 kg
GTIN	4260439550101

Usage recommendations

- high quality digital audio connection
- to connect high quality DACs using the isolated electrical or the optical output



HiFiBerry Deutschland GmbH
Corinthstrasse 53
D-10245 Berlin
Germany

sales@hifiberry.com
www.hifiberry.com