





RS270P-4A




П	ľ	П	П	D	ES
г		м.	u	$\mathbf{r}$	2

- Three-part paper composite diaphragm featuring paper, Kevlar, and glass fibers
- Low-distortion high-excursion motor system with two shortcircuit paths
- Similar cosmetics and design features as original aluminum Dayton Audio Reference Series
- Perfect for use a woofer, midwoofer, or dedicated midrange driver
- 90.9 dB sensitivity and 6 mm of excursion

PARAMETE	RS
Impedance	4 ohms
Re	3.9 ohms
Le	0.55 mH
Fs	22.9 Hz
Qms	1.35
Qes	0.34
Qts	0.27
Mms	73.2g
Cms	0.66 mm/N
Sd	346.4 cm <sup>2</sup>
Vd	207.8 cm <sup>3</sup>
BL	10.9 Tm
Vas	110.5 liters
Xmax	6.0 mm
VC Diameter	2"
SPL	90.9 dB @ 2.83V/1m
RMS Power Handling	100 watts
Usable Frequency Range (Hz)	23 - 6,000 Hz





**OmniMic** 

 $\textbf{Note:}\ 1/24^{th}\ \text{octave smoothing - nearfield response included in graph below 450 Hz}.$ 

Black = 0° Red = 15° Green = 30° Blue = 45°