

15PR450

15" - 400 W - 98 dB



NOMINAL SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	356 mm (14.02 in)
Depth	172.6 mm (6.80 in)
Flange and gasket Thickness	13.6 mm (0.54 in)
Net Weight	7.8 kg (17.2 lb)
Shipping Box	430 x 427 x 236 mm
(Single Carton Box)	(16.9 x 16.8 x 9.3 in)
Shipping Weight	8.9 kg (19.6 lb)

- NOTES:
- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
 - (2) Maximum power is defined as 3dB greater than nominal power
 - (3) Treated Polycotton
 - (4) $X_{max} = [(Winding\ Depth - magnetic\ gap\ depth) / 2] + (magnetic\ gap\ depth / 3)$
 - (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	6.2 Ω
AES Power Handling (1)	400 W
Maximum Power Handling (2)	800 W
Sensitivity (1W/1m)	98 dB
Frequency Range	35÷4000 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	15 mm (0.59 in)
Magnetic Gap Depth	9 mm (0.35 in)
Flux Density	1.15 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Accordion (4 waves)
NET Air Volume filled by Loudspeaker	4.1 dm³ (0.145 ft³)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	35 Hz
Re	5.1 Ω
Qes	0.37
Qms	6.9
Qts	0.35
Vas	235.6 dm³ (8.32 ft³)
Sd	857 cm² (132.84 in²)
Xmax (4)	6.00 mm
Xdamage (5)	23 mm
Mms	90 g
Bl	16.6 N/A
Le	0.65 mH
Mmd	61.6 g
Cms	0.23 mm/N
Rms	2.9 kg/s
η _o (Eta Zero)	2.67 %
EBP	96 Hz

