

|                                  |                      |
|----------------------------------|----------------------|
| <b>Sensitivity (2.83v/1m)</b>    | <b>88 dB</b>         |
| <b>Frequency range</b>           | <b>32 Hz - 3 KHz</b> |
| <b>Free air resonance, fs</b>    | <b>32 Hz</b>         |
| <b>DC resistance, Re</b>         | <b>6.7 Ohms</b>      |
| <b>Voice coil inductance, Le</b> | <b>1.2 mH</b>        |
| <b>Moving mass, md</b>           | <b>21 g</b>          |
| <b>Force factor, Bl</b>          | <b>8.82 Telsa</b>    |
| <b>Equivalent volume, Vas</b>    | <b>77 Ltrs</b>       |
| <b>Mechanical Q-factor, Qms</b>  | <b>3.92</b>          |
| <b>Electrical Q-factor, Qes</b>  | <b>0.35</b>          |
| <b>Total Q-factor, Qts</b>       | <b>0.32</b>          |
| <b>X-max</b>                     | <b>+/- 5.0 mm</b>    |
| <b>Voice coil diameter</b>       | <b>38 mm</b>         |
| <b>Rated power handling</b>      | <b>120 W</b>         |
| <b>Net weight</b>                | <b>2.5 Kg</b>        |

