

Thiele-Small Parameters

	Tempest 10"	Tempest 12"	Tempest 15"
Coils	Dual 4	Dual 4	Dual 4
Fs	n/a	n/a	21.8 Hz
Re	n/a	n/a	6.68 Ohm
Qms	n/a	n/a	14.91
Qes	n/a	n/a	.362
Qts	n/a	n/a	.353
Mms	n/a	n/a	249.27 g
Cms	n/a	n/a	.214
Sd	n/a	n/a	823.70cm ²
Vas	n/a	n/a	205.29 L
SPL	n/a	n/a	89.72 dB
BI	n/a	n/a	25.09 Tm
Xmax	n/a	n/a	15.1mm (One Way)
RMS	500W - Program Power 750W - Thermal	500W - Program Power 750W - Thermal	500W - Program Power 750W - Thermal

Technical Specifications

	Tempest 10"	Tempest 12"	Tempest 15"
Overall Diameter	n/a	n/a	15.625"
Cutout Diameter	n/a	n/a	14.125"
Mounting Depth	n/a	n/a	7.375" - Driver 8.375" - Driver With Pole Vent Clearance
Driver Displacement	n/a	n/a	.13 cuft
Sealed Enclosure	n/a	n/a	2-5 cuft
Ported Enclosure	n/a	n/a	3.5-7.5 cuft @ 30Hz