



5" PAPER SUBWOOFER

- LONG-THROW HIGH-POWER LOADING DESIGN( X-max=9.25mm)
- PAPER CONE WITH BIG ROLL, LESS DAMPING RUBBER SURROUND
- VENTED POLE PIECE
- STAMPING STEEL BASKET
- SUITABLE FOR SUBWOOFER APPLICATION

DIAPHRAGM MTL	Paper
SURROUND MTL	Rubber
NOMINAL IMPEDANCE	4 Ω
DCR IMPEDANCE	3.4Ω
SENSITIVITY 1W/1m	82 dB
FREQUENCY RESPONSE	45-1.5K Hz
FREE AIR RESONANCE	45 Hz
VOICE COIL DIAMETER	32 mm
AIR GAP HEIGHT	5 mm
RATED POWER INPUT	30 W
MAXIMUM POWER INPUT	60 W
FORCE FACTOR, BL	6.51 TM
MAGNET WEIGHT (oz)	Neodymium
MOVING MASS	24.95 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	478.7MN <sup>-1</sup>
EFFEC.PISTON AREA	0.0094m <sup>2</sup>
Levc	0.25mH
Zo	36ohm
X-max	9.25 mm
Vas	6.01 Liter.
Qts	0.48
Qms	2.83
Qes	0.58



VOICE:886.2.26570282 FAX:886.2.26580166  
E-MAIL :info@tb-speaker.com