



- LONG-THROW HIGH-POWER LOADING DESIGN (X-max=9.25mm)
- PAPER CONE WITH BIG ROLL, LESS DAMPING RUBBER SURROUND
- VENTED POLE PIECE
- STAMPING STEEL BASKET
- SUITABLE FOR SUBWOOFER APPLICATION

5" PAPER SUBWOOFER



DIAPHRAGM MTL	Paper
SURROUND MTL	Rubber
NOMINAL IMPEDANCE	4 W
DCR IMPEDANCE	3.4 W
SENSITIVITY 1W/1m	82 dB
FREQUENCY RESPONSE	45-1.5K Hz
FREE AIR RESONANCE	45 Hz
VOICE COIL DIAMETER	32 mm
AIR GAP HEIGHT	5 mm
RATED POWER INPUT	40 W
MAXIMUM POWER INPUT	80 W
FORCE FACTOR, BL	7.17 TM
MAGNET WEIGHT ( 19.1 oz)	540 g
MOVING MASS	28.81 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	368.72 $\mu\text{MN}^{-1}$
EFFEC.PISTON AREA	0.0094 $\text{M}^2$
Levc	0.34 mH
Zo	26 ohm
X-max	9.25 mm
Vas	4.85 Litr.
Qts	0.49
Qms	3.56
Qes	0.57



VOICE:886.2.26570282 FAX:886.2.26580166  
E-MAIL :info@tb-speaker.com