



5" PP FULL RANGE

- FULL RANGE DESIGN
- BLACK COLOR PP CONE WITH WIDE RANGE TEMPERATURE, HIGH LOSS RECIPE OF RUBBER SURROUND
- MOTOR DESIGN UNDERHUNG
- GF REINFORCED NYLON BASKET



DIAPHRAGM MTL	Black color PP
SURROUND MTL	Rubber
NOMINAL IMPEDANCE	8 W
DCR IMPEDANCE	6.3 W
SENSITIVITY 1W/1m	90 dB
FREQUENCY RESPONSE	60-20K Hz
FREE AIR RESONANCE	60 Hz
VOICE COIL DIAMETER	25.4 mm
AIR GAP HEIGHT	10 mm
RATED POWER INPUT	28 W
MAXIMUM POWER INPUT	56 W
FORCE FACTOR, BL	5.53 TM
MAGNET WEIGHT (18.6 oz)	525 g
MOVING MASS	5.99 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	1307 μMN^{-1}
EFFEC.PISTON AREA	0.0094 M^2
Levc	0.023 mH
Zo	40 ohm
X-max	3 mm
Vas	11.69 Liter.
Qts	0.44
Qms	2.80
Qes	0.52



VOICE: 886.2.26570282 FAX: 886.2.26580166
E-MAIL: info@tb-speaker.com