



8" PAPER SUBWOOFER

- LONG-THROW HIGH-POWER LOADING DESIGN(X-max=12mm)
- PAPER CONE WITH BIG ROLL, SPECIAL LESS DAMPING, WIDE RANGE TEMPERATURE RUBBER SURROUND
- VENTED POLE PIECE , NEODYMIUM MAGNET DESIGN
- STAMPING STEEL BASKET
- SUITABLE FOR SUBWOOFER APPLICATION
- MAGNETICALLY SHIELDED

| | |
|----------------------|------------------------|
| DIAPHRAGM MTL | Paper |
| SURROUND MTL | Rubber |
| NOMINAL IMPEDANCE | 4 Ω |
| DCR IMPEDANCE | 3.2 Ω |
| SENSITIVITY 1W/1m | 84 dB |
| FREQUENCY RESPONSE | 30-800 Hz |
| FREE AIR RESONANCE | 30 Hz |
| VOICE COIL DIAMETER | 49.5 mm |
| AIR GAP HEIGHT | 8 mm |
| RATED POWER INPUT | 150 W |
| MAXIMUM POWER INPUT | 300 W |
| FORCE FACTOR, BL | 14.02 TM |
| MAGNET WEIGHT (oz) | Neodymium |
| MOVING MASS | 99.78 g |
| FERRO FLUID ENHANCED | No |
| SUSPENSION COMPL. | 275.28MN ⁻¹ |
| EFFEC.PISTON AREA | 0.022M ² |
| Levc | 0.654mH |
| Zo | 79ohm |
| X-max | 12 mm |
| Vas | 18.92 Litr. |
| Qts | 0.29 |
| Qms | 4.26 |
| Qes | 0.31 |



TB SPEAKERS

VOICE:886.2.26570282 FAX:886.2.26580166
E-MAIL :info@tb-speaker.com